

<b>B2530 Technical Specification</b>		
<b>Engine</b>		
	Make:	Kubota
	Type	Indirect Injection, Water cooled, 4 cycle Diesel
	No of cylinders:	3
	Displacement: Gross Power (SAE) Max Torque:	1123cc
	Make:	18.4 kw @ 2700 RPM
	Type	72N-M
<b>Capacities:</b>		
	Fuel Tank:	27 litres
<b>Dimensions:</b>		
	Overall length:	2430mm (w/o 3p hitch)
	Overall width:	1105mm
	Overall height	2290 (ROPS)
		2090 (Cab)
	Min ground Clearance:	285mm
	Turning Radius:	2.1m
<b>Weight:</b>		
	ROPS::	750kg
	Cab :	960kg
<b>Tyres:</b>		
	Front:	6.00-12
	Rear::	9.5-18
<b>Steering:</b>		
	Hydraulic Power steering	
<b>Transmission:</b>		
	Main:	Continuously Variable Hydrostatic
	Range	3 gears
<b>Brakes:</b>		
	Wet Disc	
<b>Hydraulics:</b>		
	Pump capacity:	20.5 litres/min
	3 Pt lift:	Cat I
	Max Lift:	970kg at lift ends 760kg 600mm behind lift ends
<b>PTO Power:</b>		
		14kw
<b>PTO:</b>		
	Rear:	540 RPM
	Mid:	2500 RPM
	Speed	Forward: 23km/h
		Reverse 18km/h