

BX24-SPECIFICATIONS

Engine	Type	E-TVCS liquid cooled, 3-cylinder diesel	
	Make, Model	HP (kW)	Kubota D902
	PTO Horsepower	HP (kW)	17.7 (13.2)
	Engine gross horsepower	HP (kW)	23.0 (17.2)
	Rated RPM		3200
	Bore and stroke	in. (mm)	2.8 x 2.9 (72x73.6)
	Total displacement	cu.in. (cc)	54.8 (898)
	Air Cleaner		Dry paper dual element
	Lubrication		Forced lubrication
	Cooling System		Pressurized radiator
Radiator fan		Radial air flow	
Capacities	Fuel tank	gal. (l)	6.6 (25)
	Cooling system	qts. (l)	2.8 (2.7)
	Engine oil	qts. (l)	3.3(3.1)
	Transmission case	gal. (l)	3.1(11.6)
Drive Train	Clutch	N/A	
	Transmission	HST (2 range)	
	Differential lock	Standard	
	Final drive	Spur gear	
	Brake	Multi wet disc	
	PTO	Hydraulic Independent	
	Rear	540 rpm at 3068 engine rpm	
	Mid	2500 rpm at 3125 engine rpm	
Hydraulics	Type	Open center	
	Pump	Gear Type	
	Total pump output	gpm (l/min)	6.3(24.0)
	Hydraulic outlet	Block (Mid & Rear)	
	3 -point hitch	Category I	
	Hydraulic control system	Quarter Inching Valve	
	Lift capacity (at lift point) (24 in. behind LP)	lbs. (kg)	992 (450)
		lbs. (kg)	661 (300)
Steering	Hydrostatic power steering		
Standard Tire Size	Front	18x8.50 -10 Turf	
	Rear	26x12.00 -12 Turf	
Traveling Speeds (at rated engine rpm)	Forward	mph (km/h)	0-8.1
	Reverse	mph (km/h)	0 - 6.2
Dimensions	Overall length (with 3P)	in. (mm)	95.5 (2425)
	Overall width (min. tread)	in. (mm)	32.3(820)
	Wheel base	in. (mm)	55.1 (1400)
	Ground clearance	in. (mm)	8.7 (220)
	Turning radius w/o brake	ft (m)	7.5 (2.3)
	Weight with ROPS	lbs.(kg)	1542(700)

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.