

MF 160 Specifications:

S=Standard op=Optional na =Not applicable/available

Model		MF 163F	MF 167 V	MF 169 V
Bale size				
DIAMETER	M	1.25	0.60 - 1.65	0.60 - 1.95
WIDTH	M	1.20	1.20	1.20
Bale chamber				
TYPE		FIXED	VARIABLE	VARIABLE
BALE FORMING SYSTEM		CHAIN AND SLAT, PLUS ROLLERS	5-BELTS PLUS SUPPORT ROLLERS	5-BELTS PLUS SUPPORT ROLLERS
FEEDING SYSTEM			RAKE / ROTOR / CUTTER	ROTOR / CUTTER
Pickup				
PICKUP WIDTH OPTIONS	M	2.00 / -	2.00 / 2.20	2.20 / -
NUMBER OF TINE BARS / TINES				
- 2.0 M PICKUP		4 / 112 TOTAL	4 / 112 TOTAL	na
- 2.2 M PICKUP		na	5 / 160 TOTAL	5 / 160 TOTAL
WIDE ANGLE DRIVE SHAFT		S	S	S
HYDRAULIC PICKUP LIFT		S	S	S
PICKUP WHEEL		2	2	2
SUPERCUT 14-KNIFE CUTTER WITH ELECTRO-HYDRAULIC REVERSER		na	op	op
Bale tying system				
TWIN TWINE AUTO START		S	S (OPTIONAL WITH CUTTER)	S (OPTIONAL WITH CUTTER)
NET WRAP		S	S	S
NUMBER OF TWINE BALLS		4	6	6
NUMBER OF NET ROLLS		1	2	2
MONITORING		IN-CAB, ELECTRONIC	IN-CAB, ELECTRONIC	IN-CAB, ELECTRONIC
Tyres				
	S	11.5/80-15	15.0/55-17	15.0/55-47
	op	-	19.0/45-17	19.0/45-17
Tractor requirements				
PTO HORSEPOWER	HP (KW)	FROM 80 (60)	FROM 100 (75)	FROM 100 (75)
PTO SPEED	REV/MIN	540	540	540
HYDRAULIC OUTLETS		TWO, SINGLE ACTING	TWO, DOUBLE ACTING	TWO, DOUBLE ACTING
Dimensions and weights				
OVERALL WIDTH - 2.0 M PICKUP	M	2.25	2.32	-
- 2.2 M PICKUP	M	-	2.52	2.52
OVERALL LENGTH	M	3.70	4.48	4.75
OVERALL HEIGHT	M	2.08	2.70	2.95
WEIGHT	KG	2320	2990 (LESS CUTTER)	3700 (LESS CUTTER)
Lubrication				
AUTO LUBRICATION		S	S	S
CENTRALISED GREASING		S	S	S
Optional equipment	AUTO LUBRICATION (MF 163F), BALE RAMP, SPARE NET HOLDER, SHORT CROP KIT, STRAW PLATE, HYDRAULIC BRAKES, AIR BRAKES			