



540/1000 REV/MIN PTO		-	-	-	-	-	-	○	○	○
<b>Linkage and hydraulics</b>										
FUNCTIONS		DRAFT CONTROL, POSITION CONTROL, RESPONSE CONTROL								
MAX OIL FLOW/PRESSUR E	LITRE/MIN / BAR	17/210	17/210	17/210	17/210	17/210	17/210	17/210	17/210	17/210
MAXIMUM LIFT CAPACITY AT LINK ENDS	KG	2100	2100	2500	2500	2500	2500	3200	3200	3200
<b>Auxiliary hydraulics</b>										
MAX OIL FLOW/PRESSUR E	LITRE/MIN / BAR	17/210	17/210	42/170	42/170	42/170	42/170	50/170	50/170	50/170
CONTROL		1 DOUBLE ACTING SPOOL VALVE WITH SPRING-TO-NEUTRAL FACILITY (PLUS SELECTOR VALVE MF 415/MF 415N)								
<b>'Standard' wheels and tyres</b> (FULL RANGE AVAILABLE PLEASE CONSULT YOUR DEALER)										
FRONT - 2WD PRESSED WHEELS		6.00-16	6.00-16	7.50-16	7.50-16	6.00-16	7.50-16	9.00-16	9.00-16	9.00-16
- 4WD PRESSED WHEELS		12.5/80-18	7.00-18	12.4-24	12.4-24	7.00-18	12.4-24	14.9-24	14.9-24	14.9-24
REAR PRESSED WHEELS		14.9-24	14.9-24	18.4-30	18.4-30	14.9-24	18.4-30	18.4-34	18.4-34	18.4-34
<b>Weights and dimensions</b> (APPROXIMATE WITH 'STANDARD' WHEELS AND TYRES LESS FUEL)										
WEIGHT - 2WD/4WD	KG	2030/2210	2030/2210	2590/2870	2590/2870	2155/2866	2620/3040	3575/3940	3626/4210	4120/4520
<b>Dimensions</b>										
OVERALL LENGTH - 2WD/4WD	M	3.84/3.84	3.47/3.47	3.98/4.13	3.98/4.13	3.60/3.60	3.98/4.13	4.25/4.32	4.56/4.63	4.56/4.63
OVERALL HEIGHT										
- OVER EXHAUST/SUN CANOPY	M	2.10/2.44	-	2.44/2.58	2.44/2.58	-	2.44/2.58	2.80/2.64	2.80/2.64	2.80/2.64
- OVER STEERING WHEEL	M	-	1.57	-	-	1.57	-	-	-	-

WHEELBASE - 2WD/4WD	M	2.00/2.00	2.01/2.01	2.14/2.37	2.14/2.37	2.14/2.14	2.14/2.37	2.37/2.46	2.71/2.73	2.71/2.73
‡ MEASURED TO FRONT OF WEIGHT FRAME										
<b>Capacity</b>										
FUEL TANK	LITRE	57	57	75	75	75	75	210	210	210