

MF 5300 Specifications:

• = STANDARD

○ = OPTIONAL

— = NOT APPLICABLE/AVAILABLE

Models		MF 5340	MF 5355	MF 5360	MF 5365
Performance					
RATED ENGINE POWER *ISO @ 2200 REV/MIN ‡DIN	HP (kW)	82 (61.1)	92 (68.6)	105 (78.3)	120 (89.5)
	PS (kW)	80 (58.8)	90 (66.2)	102 (75)	115 (84.6)
MAX. TORQUE @ REV/MIN	*NM/ REV/MIN	288/1400	348/1400	382/1400	442/1200
MAX PTO POWER @ RATED ENGINE SPEED †DIN	PS (kW)	71 (53)	79.8 (59.6)	90.9 (67.8)	102.1 (76.2)
*ISO TR14396 †DIN 70020					
Engine					
PERKINS, WATER COOLED, DIRECT INJECTION DIESEL	TYPE	P4001	P4001T	P4001T	1006.6
	ASPIRATION	NATURAL	TURBO	TURBO	NATURAL
CAPACITY/NO. OF CYLINDERS	LITRE/NO.	4.1/4	4.1/4	4.1/4	6/6
EXHAUST ASPIRATED AIR CLEANER		•	•	•	•
Transmission					
12 FORWARD, 4 REVERSE SYNCHROMESH - (30 KM/H)		•	•	•	•
12 FORWARD 4 REVERSE, SYNCHROMESH - (40 KM/H)		○	○	○	○
12 FORWARD, 12 REVERSE, MANUAL SHUTTLE		○	○	○	○
Power take-off					
TYPE		— SINGLE SPEED, INDEPENDENT PTO. 540 REV/MIN @ 2000 ENGINE REV/MIN. 35 MM (13/8IN) 6-SPLINE SHAFT			
540/1000 REV/MIN SHIFTABLE PTO		○	○	○	○
Linkage and hydraulics					
FUNCTIONS		———— DRAFT CONTROL POSITION CONTROL RESPONSE CONTROL ————			
CONTROL - MECHANICAL/ELECTRONIC		•/○	•/○	•/○	•/○
MAX OIL FLOW/PRESSURE	LITRE/MIN / BAR	28/210	28/210	28/210	28/210
MAXIMUM LIFT CAPACITY AT	KG	•2600/○4000	•2600/○4000	•2600/○4000	•2600/○4000

LINK ENDS					
Auxiliary hydraulics					
MAX OIL FLOW/PRESSURE	LITRE/MIN / BAR	66/210	66/210	66/210	66/210
CONTROL		— SELECTOR VALVE PLUS 1 SINGLE/DOUBLE ACTING SPOOL VALVE (2, OPTIONAL) WITH SPRING-TO-NEUTRAL FACILITY —			
Operator Area					
PLATFORM		• — RUBBER MOUNTED, SPRING SUSPENSION SEAT, SAFETY FRAME AND SUN CANOPY —			
SAFETY CAB		○ — SOUND INSULATED, WITH AIR CONDITIONING —			
'Standard' wheels and tyres (FULL RANGE AVAILABLE, PLEASE CONSULT YOUR DEALER)					
FRONT - 2WD, PRESSED WHEELS		9.00-16	9.00-16	9.00-16	9.00-16
- 4WD, PRESSED WHEELS		14.9-24	14.9-24	14.9-24	14.9-24
REAR PRESSED WHEELS		18.4-34	18.4-34	18.4-34	18.4-34
Weights and dimensions (APPROXIMATE, WITH 'STANDARD' WHEELS AND TYRES, LESS FUEL)					
WEIGHT - PLATFORM 2WD/4WD	KG	3170/3652	3170/3652	3170/3652	3800/4032
- SAFETY CAB 2WD/4WD	KG	3390/3912	3390/3912	3390/3912	4040/4232
Dimensions					
OVERALL LENGTH - 2WD/4WD	M	4.01/4.01	4.01/4.01	4.01/4.01	4.32/4.45
OVERALL HEIGHT					
- OVER SUN CANOPY/SAFETY CAB	M	2.63/2.66	2.63/2.66	2.63/2.66	2.71/2.79
WHEELBASE	M	2.35	2.35	2.35	2.61
‡ MEASURED TO FRONT OF WEIGHT FRAME					
Capacity					
FUEL TANK	LITRE	•125/○200	•125/○200	•125/○200	•200